

# 日立交流无刷重型冲击扳手

22mm

WR 22SE  
AC-powered



25mm

WR 25SE  
AC-powered



## 规格参数

型号		WR 22SE	WR 25SE
能力	普通螺栓	14 - 24mm (9/16 - 1")	22 - 30mm (7/8 - 1-3/16")
	高强度螺栓	16 - 22mm (5/8 - 7/8")	22 - 24mm (7/8 - 1")
拧紧扭矩		620Nm (5,490in.-lbs.)	1,000Nm (8,850in.-lbs.)
驱动方头规格		3/4" (19mm)	1" (25.4mm)
空载转速		1,400/min.	1,100/min.
冲击速率		2,000/min.	1,500/min.
全长		280mm (11")	340mm (13-3/8")
重量 *1		4.6 kg (10.1 lbs.)	7.7 kg (17.0 lbs.)
振动值 (三轴合计) *2		Vibration emission value $a_h = 15.2 \text{ m/s}^2$ Uncertainty $K = 1.5 \text{ m/s}^2$	
标准附件		侧手柄, 携带箱	

\*1: According to EPTA-Procedure 01/2003.

\*2: The tri-axial vibration values were measured according to EN60745.

Distributed by:

Hitachi Koki Co., Ltd.

www.hitachi-koki.cn

日立交流无刷重型冲击扳手  
22mm (7/8") WR 22SE  
25mm (1") WR 25SE

NEW

HITACHI  
Inspire the Next

# 紧凑 轻量 大扭矩!

HITACHI IMPACT WRENCHES WR 22SE / WR 25SE

拧紧扭矩

620Nm

WR 22SE

拧紧扭矩

1,000Nm

WR 25SE



日立  
原创

高效率 & 免碳刷维护

日立交流无刷马达



坚固 & 高耐用性

铝壳双重绝缘机身结构



WR 22SE

\*1 As of November 2014. Among 22/25mm-class impact wrenches made by leading power tool manufacturers. (surveyed by Hitachi Koki.)  
\*2 As of November 2014. Among impact wrenches made by leading power tool manufacturers. (surveyed by Hitachi Koki.)

